# DESCRIPTIVE FEATURES OF PARKER'S O-LUBE P/N: OLUBE 884-x

Date: 01/26/2021

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

# **Description:**

Ingredients Barium Soap 25-30% Base Oil 70-75% **Water Content** 0.2% max. **Grease Number** #2 NLGI Pour Point (open cup) 485°F max. 435°F min. Flash Point (open cup) **Fire Point** 485°F min. ASTM D217 Penetration @ 77°F 265-295 **ASTM Drop Point** 400°F min.

Ash Sulfate 14.25% max.

Specific Gravity Less than 1.0 (.9007 to .9129)

# **Physical Data:**

Boiling Point (°F) 700

Specific Gravity Less than 1.0

Vapor Pressure N/A
Percent, Volatile by Volume (%) N/A
Vapor Density (Air=1) N/A

**Evaporation Weight**Solubility in Water
Less than 1.0
Negligible

Appearance and Odor Semi-Solid, Amber Color, No Odor

Trade Name: Parker O-Lube Revision: Initial Release Page: 1 out of 8

## **SAFETY DATA SHEET**

Date Prepared: 01/26/2021 Date Reviewed: 1/26/2021

Section I

Trade Name Parker O-Lube Part number(s) OLUBE 884-xx

Supplier's Name Parker Hannifin O-Ring & Engineered Seals Division

2360 Palumbo Drive, PO Box 11751, Lexington, KY 40512

oesmailbox@parker.com

Information Department Engineering

**Emergency Telephone No.** During normal business hours: (859) 269-2351

## Section II - Hazards Identification

Classification of the substance or mixture



Asp. Tox. 1 H304 May be fatal if swallowed and enters airways

\_\_\_\_\_\_



Acute. Tox. 4 H332 Harmful if inhaled

\_\_\_\_\_\_

Label elements

GHS Label elements: The product is classified and labeled according to the Globally Harmonized System

Hazard Pictograms







Signal word Danger

## Hazard-determining components of labeling:

Barium, acetate tallow fatty acids complex
Distillates (petroleum), hydrotreated heavy naphthenic

(continued on page 2)

(continued from page 1)

Page: 2 out of 8

#### Hazard Statements

Harmful if swallowed

May be fatal if swallowed and enters airways

# **Precautionary Statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only in a well-ventilated area

If swallowed: Immediately call a poison center / doctor

Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center / doctor if you feel unwell.

Store locked up.

Dispose of contents / container in accordance with local/regional/national/international regulations.

## Classification system: NFPA ratings (scale 0-4)



# HMIS-ratings (scale 0-4)



## Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable vPvB: Not applicable

# Section III - Composition / Information on Ingredients

Chemical characterization: Mixture

**Description:** Mixture of the substances listed below with nonhazardous additions.

## Dangerous components

Distillates (petroleum), hydrotreated heavy naphthenic CAS #64742-52-5 10-30% by weight Barium, acetate tallow fatty acids complex CAS #68201-19-4 10-30% by weight

## **Section IV – First Aid Measures**

## Description of first aid measures

## General Information

Symptoms of poisoning may even occur after several hours; therefore, medical observation for at least 48 hours after the accident

## After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness, place patient stably in side position for transportation.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

## Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

## Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Trade Name: Parker O-Lube Revision: Initial Release Page: 3 out of 8

## **Section V – Fire Fighting Measures**

## Extinguishing media

- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available. Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## Section VI - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Not required.

**Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## Protective Action Criteria for Chemicals

PAC-1:

None of the ingredients is listed.

PAC-2:

None of the ingredients is listed.

PAC-3:

None of the ingredients is listed.

# Section VII - Handling and Storage

#### Handling:

## Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

**Specific end use(s)** No further relevant information available.

# Section VIII - Exposure Controls / Personal Protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Additional information: The lists that were valid during the creation were used as basis.

**Exposure controls** 

Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

(continued on page 4)

Trade Name: Parker O-Lube Revision: Initial Release Page: 4 out of 8

(continued from page 3)

## Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

## Penetration time of glove material

The exact break through time must be determined by the manufacturer of the protective gloves and must be observed.

Eye protection: Goggles recommended during refilling.

# **Section IX – Physical and Chemical Properties**

Information on basic physical and chemical properties

**General Information** 

Appearance:

Form: Semi-Solid
Color: Amber colored

Odor: Petroleum-like

Odor threshold: Not determined. pH-value: Not determined. Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: 370 °C (698 °F)

Flash point: 190 °C (374 °F)

Flammability (solid, gaseous): Not applicable. Ignition temperature: >315 °C (>599 °F)
Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.

**Danger of explosion:** Product does not present an explosion hazard.

**Explosion limits:** 

Lower: Not determined.
Upper: Not determined.
Vapor pressure: Not determined.

Density at 20 °C (68 °F): 0.93389 g/cm³ (7.79331 lbs/gal)

Relative density Not determined. Vapor density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

·(continued on page 5)

Trade Name: Parker O-Lube Revision: Initial Release Page: 5 out of 8

(continued from page 4)

Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Solvent content: Water: 0.0 %

> VOC content: 0.00 % 0.0 g/l / 0.00 lb/gal Solids content: 20.0 %

Other information No further relevant information available.

# Section X - Stability and Reactivity

**Reactivity** No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available. **Incompatible materials:** No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

# Section XI - Toxicological Information

Information on toxicological effects

Acute toxicity:

Primary irritant effect:

on the skin: No irritant effect. on the eye: No irritating effect. **Sensitization:** No sensitizing effects known. Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for

preparations: Harmful Carcinogenic categories

OSHA-Ca (Occupational Safety & Health Administration): (Substances not listed)

None of the ingredients is listed.

# Section XII - Ecological Information

**Toxicity** 

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects No further relevant information available.

# **Section XIII – Disposal Considerations**

## Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. **Uncleaned packagings:** 

**Recommendation:** Disposal must be made according to official regulations.

# **Section XIV – Transport Information**

**UN-Number** 

DOT, IMDG, IATA UN3287

UN proper shipping name

**DOT** Toxic liquid, inorganic, n.o.s. (Barium, acetate tallow fatty

acids complex)

IMDG, IATA TOXIC LIQUID, INORGANIC, N.O.S. (Barium, acetate

tallow fatty acids complex)

# Transport hazard class(es)

DOT



Class 6.1 Toxic substances

Label 6.1

\_\_\_\_\_\_

## IMDG, IATA



Class 6.1 Toxic substances

Label 6.1

-----

Packing group

DOT, IMDG, IATA

Environmental hazards:

Marine pollutant: No

**Special precautions for user**Warning: Toxic substances

**Hazard identification number (Kemler code):** 60 **EMS Number:** F-A,S-A

Stowage Category A

**Stowage Code** SW2 Clear of living quarters.

(continued on page 7)

(continued from page 6)

Page: 7 out of 8

Transport in bulk according to Annex II

of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT

**Quantity limitations**On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L

**IMDG** 

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (BARIUM,

UN "Model Regulation":

UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (BARIUM ACETATE TALLOW FATTY ACIDS COMPLEX), 6.1, III

# Section XV – Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

68201-19-4 Barium, acetate tallow fatty acids complex 10-30%

TSCA (Toxic Substances Control Act):

68201-19-4 Barium, acetate tallow fatty acids complex ACTIVE 10-30%

Hazardous Air Pollutants

None of the ingredients is listed.

**Proposition 65** 

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

## Hazard pictograms





GHS07

GHS08

Signal word Danger

(continued on page 8)

(continued from page 7)

Page: 8 out of 8

## Hazard-determining components of labeling:

Barium, acetate tallow fatty acids complex

Distillates (petroleum), hydrotreated heavy naphthenic

## Hazard statements

Harmful if inhaled.

May be fatal if swallowed and enters airways.

## Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only in a well-ventilated area.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## Section XVI - Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Engineering

Contact: Mr. Ewing

Date of preparation / last revision 1/26/2021 / --

## Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health Acute Tox. 4: Acute toxicity – Category 4 Asp. Tox. 1: Aspiration hazard – Category 1

Prepared by: Parker Hannifin O-Ring & Engineered Seals Division

These data are offered in good faith as typical values and not as product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.